

## Ascom d41 DECT Handset, Basic

### Features

- GAP/CAP compliant DECT handset
- Dynamic output power
- High quality voice
- Large illuminated B/W and grey scale display
- Local phonebook
- Very simple usage
- Voice mail
- Manual and automatic keypad lock
- Clear lists in charger
- Call list with the 25 last calls
- Easy access to PBX services
- Loudspeaking function
- Vibrator
- Easy replacement
- 11 languages and 1 customizable
- Standard headset connector 2.5 mm
- Upgradeable with licence



### Technical Specifications

#### Physical

Dimension (l x w x d):	133 x 53 x 24 mm
Weight:	115 g (battery and clip included)
Material:	Case: PC-ABS, Key pad: Silicone, Clip: POM
Colour:	Grey
Display (w x h):	28 x 35 mm, FSTN B/W
Clip:	Hinge type (standard) or swivel type

#### Battery and charging

Type:	600 mAh (Li-Ion)
Speech time:	16 h during optimal condition
Stand-by time:	180 h during optimal condition
Charge time:	< 4 h
Discharge/charge cycles:	>=65% capacity left after 500 full charge/discharge cycle.

#### Connectors

Multi-purpose connector:	For battery charging, software download, and configuration
Headset connector:	Standard 2.5 mm

#### User interface

Display (w x h):	112 x 115 pixels, with white LED backlighting.
Indicator:	LED on top/front for visual indication of incoming call, and charging.
Vibrator:	Incoming call

Keypad:

- Soft keys
- Hook off key
- On hook and Power On/Off on the same key
- Four way navigation key
- Numerical keys

### **Audio**

Ring signal: Adjustable in 8 steps  
Earpiece: Adjustable in 8 steps of 3dB each  
Maximum sound pressure level: 88 dBA @ 10 cm  
Loudspeaker: Duplex loud speaking function

### **Settings**

Languages: 11 preinstalled (Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Portuguese (Brazilian), Spanish, Swedish).  
  
One additional programmable. 7 languages available for download (Czech, Greek, Hungarian, Polish, Russian, Slovakian, and Turkish).

### **Local Phonebook**

Storage of contacts:

- 48 character name
- 24 digit work number
- 24 digit mobile phone number
- 24 digit other numbers

Entries 250

### **Telephony**

Indication: 14 ring signals, flashing LED and vibrator.  
Answer call options: Button press or auto answer  
Call list storage capacity: 25 calls (received, dialled and missed) with time stamp

### **Radio**

Automatic DECT protocol detection: Automatic detection and configuration for US DECT and EU DECT at first registration.

Frequency range:

- EU: 1880-1900 MHz
- US: 1920-1930 MHz
- LA: 1910-1930 MHz
- BR: 1910-1920 MHz
- -- : 1900-1920 MHz

Modulation: GFSK  
Channel spacing: 1.728 MHz  
Antenna: Integral  
Sensitivity: -93 dBm  
Radiated power: EU: 250 mW  
US: 100 mW

*Specifications are subject to change without notice.*

## Environmental

Operating temperature:	0°C to +40°C
Storage temperature <sup>1</sup> :	-20°C to +60°C
Enclosure protection:	IP40, IEC EN60529
Immunity to ESD:	4 kV contact discharge and 8 kV air discharge (EN61000-4-2)
Immunity to electromagnetic fields:	3 V/m EN61000-4-3
Free fall test, standard product:	IEC 60068-2-32, procedure 1, dropped 12 times from 1 metre.

## Accessories

- Leather case
- Swivel type clip
- Hinge type clip
- Security cord
- Desktop charger Basic
- Desktop charger Advanced
- Charging Rack
- Headset with microphone on cable, DTX 9016
- Headset with microphone on boom, DTX-9017

## Compliance to European regulations and standards

EU directives:	1999/5/EC (R&TTE)
Product marking:	CE
DECT Radio:	EN 301 406, TBR22
SAR (Specific Absorption Rate):	EN50360 and EN62209-1, 0.075 W/kg (10 gram)
Safety:	EN60950-1
EMC:	EN301489- 6, EN 301 489-1

## Compliance to US regulations and standards

Product marking:	FCC ID: BXZDH3 US: 9FVW4NANDH3 HAC
SAR (Specific Absorption Rate):	FCC/OET Bulletin 65 Supplement C and IEEE Std. 1528 / ANSI/IEEE Std. C95.1 Normal operation 0.043 W/kg (1 gram) Body worn operation 0.037 W/kg (1 gram)
Safety:	UL 60950-1
EMC/Radio:	FCC Part 15 D
Hearing aid:	47 CFR Part 68, Subpart D and TIA-968-A


1. Note that storing Li-Ion batteries at high temperature dramatically reduces its capacity. For example storage around maximum temperature reduces capacity with 20% in less than a month, permanently.

*Specifications are subject to change without notice.*

### **Compliance to Canadian regulations and standards**

Product marking: IC:3724B-DH3  
SAR (Specific Absorption Rate): IEEE Std C95.1  
Normal operation 0.043 W/kg (1 gram)  
Body worn operation 0.037 W/kg (1 gram)  
Safety: CSA 60950-1  
EMC/Radio: RSS 213, ICES-003  
Hearing aid: CS-03

### **Compliance to Australian regulations and standards**

Product marking:   
Radio: EN301 406  
SAR (Specific Absorption Rate): EN50360 and EN62209-1, 0.075 W/kg (10 gram)  
Safety: AS/NZS 60950  
EMC: EN301 489-1 and EN301 489-6  
DECT: AS/ACIF S004, TS028

*Specifications are subject to change without notice.*